

TECHNICAL DATA

READY-TO-USE SQUEAKY CLEANER Typical Properties and Directions for Use

B1126

PRODUCT DESCRIPTION

Basic Coatings Ready-To-Use Squeaky Cleaner cleans hardwood floors without the residue left behind by other detergents. Squeaky is recommended for cleaning prior to recoating, as well as for general maintenance cleaning of wood floors. Squeaky is also ideal for cleaning laminate floors and is the second cleaning step of the TyKote® Dustless Recoating System.

TYPICAL PROPERTIES

Color	.Light Blue Liquid
Freeze Thaw	Stable
Flashpoint	.>200 degrees F
VOC	.Maximum VOC does not
	exceed 3.0% by weight

PACKAGING

1 U.S. gallon plastic jug (4 per case)1 U.S. quart plastic container (6 per case)

DIRECTIONS FOR USE

- 1. Sweep or vacuum the wood floor.
- 2. Spray *Squeaky Cleaner* on a Basic Coatings Microfiber Mop and wipe the surface clean.
- 3. To prevent redeposit of dirt and oil, clean the microfiber as needed. Pay special attention to corners.

Do not pour Squeaky directly on the wood floor. Excess liquid on any hardwood floor may damage the fibers. Do not use this product with any wax-finished floors.

OBLIGATION OF MANUFACTURER/SELLER

The following is made in lieu of all warranties expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for injury, loss or damage, direct or incidental or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.

1/11